















BT1855-E KIT BRAD NAILER-CT/ST 55MM MAX

BT13

Diameter: 1 - 1.25mm
Length: 15 - 55mm



Features

 Magnesium Housing	 Rubber Comfort Grip	 No-Mar-Tip	 Dial-A-Depth
 Anti Slip Bumpers	 Oil Free Engine	 Rear Exhaust	 Compact Nose
 Side Loading	 Carry Case	 Tool Lock-Out	 Selectable Trigger
 Locking Trigger	 Belt Hook		

SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.23 kg			70.00 - 120.00 PSI
Width	70 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.33
Length	235 mm		Air fitting thread type	1/4 BSP
Height	240 mm		Noise	LPA 1sd 83.20
Magazine capacity (max)	100			LWA 1sd 88.50
BT13 Series Fasteners:				LPA 1s, 1m 75.50
Diameter (mm)	1 (min)	1.25 (max)	Vibration / Uncertainty	2.8 / 1.4 m/s ²
Length (mm)	15 (min)	55 (max)		
Head (mm)	2 (min)	2 (max)		