

N64099-1-E


FAC COIL NAILER-CT 64MM





Diameter: 2.3 - 2.5mm
Length: 30 - 65mm





Features


- 


Aluminium Housing
- 


Rubber Comfort Grip
- 


Adjustable Exhaust
- 


Contact Trip
- 


Steel Frame Protectors
- 

Bench Stability
- 

Impact Resistant Magazine
- 

Compact Nose
- 

Twist Magazine
- 

Dust & Debris Guard
- 

Hanging Port

SPECIFICATION

Power type	Pneumatic	Operating pressure	4.80 - 8.30 BAR
Weight	2.63 kg		70.00 - 120.00 PSI
Width	133 mm	Air Consumption Ltr.per shot @ 5.6 bar	1.21
Length	266 mm	Air fitting thread type	1/4 BSP
Height	327 mm	Noise	LPA 1sd 93.00
Magazine capacity (max)	300		LWA 1sd 99.10
F Series Fasteners:			LPA 1s, 1m 86.10
Diameter (mm)	2.3 (min) 2.5 (max)	Vibration / Uncertainty	2.54 / 1.27 m/s ²
Length (mm)	30 (min) 65 (max)		
Head (mm)	6.5 (min) 6.5 (max)		
Collation angle	15		