

216SJK-E

SJK STAPLER 16MM (216)



Diameter: 0.6 - 0.7mm
Crown: 4.1 - 4.1mm
Length: 4 - 16mm



Features



Aluminium Housing



Rubber Comfort Grip



Power Adjustment



Secondary Trigger



Rear Exhaust



Bottom Loading

SPECIFICATION

| | | | | |
|-------------------------|-----------|-----------|--|------------------------------|
| Power type | Pneumatic | | Operating pressure | 4.90 - 8.40 BAR |
| Weight | 0.81 kg | | | 80.00 - 120.00 PSI |
| Width | 40 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 0.17 |
| Length | 221 mm | | Air fitting thread type | 1/4 BSP |
| Height | 150 mm | | Noise | LPA 1sd 64.40 |
| Magazine capacity (max) | 167 | | | LWA 1sd 74.00 |
| SJK Series Fasteners: | | | | LPA 1s, 1m 61.00 |
| Diameter (mm) | 0.6 (min) | 0.7 (max) | Vibration / Uncertainty | < 2.5 / N/A m/s ² |
| Crown (mm) | 4.1 (min) | 4.1 (max) | | |
| Length (mm) | 4 (min) | 16 (max) | | |