

# 5165043

## S4/16NC STAPLER-CT 50MM MAX (VULCANO)



Diameter: 1.4 - 1.6mm  
Crown: 12.45 - 12.7mm  
Length: 25 - 50mm



### Features



Aluminium Housing



Rubber Comfort Grip



Contact Trip

### SPECIFICATION

|                         |             |            |  |                            |
|-------------------------|-------------|------------|--|----------------------------|
| Power type              | Pneumatic   |            | Shots per charge                       |                            |
| Weight                  | 2.10 kg     |            | Operating pressure                     | 4.50 - 8.30 BAR            |
| Width                   | 80 mm       |            |  | 65.00 - 120.00 PSI         |
| Length                  | 350 mm      |            | Air Consumption Ltr.per shot @ 5.6 bar | 1.8                        |
| Height                  | 280 mm      |            | Air fitting thread type                | 1/4 BSP                    |
| Magazine capacity (max) | 136         |            | Noise                                  | <b>LPA 1sd</b> 86.50       |
| S4 Series Fasteners:    |             |            |  | <b>LWA 1sd</b> 99.00       |
| Diameter (mm)           | 1.4 (min)   | 1.6 (max)  |  | <b>LPA 1s, 1m</b> 86.00    |
| Crown (mm)              | 12.45 (min) | 12.7 (max) | Vibration / Uncertainty                | 3.6 / 1.8 m/s <sup>2</sup> |
| Length (mm)             | 25 (min)    | 50 (max)   |  |                            |