

650S4-1

S4/16NC STAPLER-CT 50MM MAX (650)



Diameter: 1.4 - 1.6mm
 Crown: 12.45 - 12.7mm
 Length: 25 - 50mm



Features



Aluminium Housing



Rubber Comfort Grip



Dial-A-Depth



Adjustable Exhaust



Contact Trip



Anti Slip Bumpers



Jam Free Design

SPECIFICATION

| | | |
|-------------------------|-------------|------------|
| Power type | Pneumatic | |
| Weight | 2.05 kg | |
| Width | 84 mm | |
| Length | 363 mm | |
| Height | 272 mm | |
| Magazine capacity (max) | 100 | |
| S4 Series Fasteners: | | |
| Diameter (mm) | 1.4 (min) | 1.6 (max) |
| Crown (mm) | 12.45 (min) | 12.7 (max) |
| Length (mm) | 25 (min) | 50 (max) |

| | | |
|--|------------------------------|-------|
| Operating pressure | 4.20 - 8.40 BAR | |
| | 60.00 - 120.00 PSI | |
| Air Consumption Ltr.per shot @ 5.6 bar | 0.65 | |
| Air fitting thread type | 1/4 BSP | |
| Noise | LPA 1sd | 76.60 |
| | LWA 1sd | 82.70 |
| | LPA 1s, 1m | 69.70 |
| Vibration / Uncertainty | 3.22 / 1.61 m/s ² | |