


BRT130-E

21° BRT STICK NAILER-ST 130MM MAX



Diameter: 3.8 - 3.8mm
Length: 100 - 130mm



Features



Aluminium Housing



Rubber Comfort Grip



No-Mar-Tip



Sequential Trip



Auxiliary Handle

SPECIFICATION

| | | | | |
|--------------------------|-----------|-----------|--|-------------------------------|
| Power type | Pneumatic | | Operating pressure | 5.00 - 8.40 BAR |
| Weight | 6.20 kg | | | 72.00 - 120.00 PSI |
| Width | 139 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 7 |
| Length | 546 mm | | Air fitting thread type | 3/8 BSP |
| Height | 445 mm | | Noise | LPA 1sd 94.32 |
| Magazine capacity (max) | 46 | | | LWA 1sd 103.02 |
| BRT 21 Series Fasteners: | | | | LPA 1s, 1m 90.02 |
| Diameter (mm) | 3.8 (min) | 3.8 (max) | Vibration / Uncertainty | 4.27 / 2.135 m/s ² |
| Length (mm) | 100 (min) | 130 (max) | | |
| Head (mm) | 9 (min) | 9 (max) | | |
| Collation type | Plastic | | | |
| Collation angle | 21 | | | |