















# BT1855-E KIT BRAD NAILER-CT/ST 55MM MAX

**BT13**

Diameter: 1 - 1.25mm  
Length: 15 - 55mm



## Features

- |                                                                                                     |                                                                                                       |                                                                                                   |                                                                                                          |
|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
|  Magnesium Housing  |  Rubber Comfort Grip |  No-Mar-Tip      |  Dial-A-Depth         |
|  Anti Slip Bumpers |  Oil Free Engine    |  Rear Exhaust   |  Compact Nose        |
|  Side Loading     |  Carry Case        |  Tool Lock-Out |  Selectable Trigger |
|  Locking Trigger  |  Belt Hook         |                                                                                                   |                                                                                                          |

## SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.23 kg			70.00 - 120.00 PSI
Width	70 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.33
Length	235 mm		Air fitting thread type	1/4 BSP
Height	240 mm		Noise	<b>LPA 1sd</b> 83.20
Magazine capacity (max)	100			<b>LWA 1sd</b> 88.50
BT13 Series Fasteners:				<b>LPA 1s, 1m</b> 75.50
Diameter (mm)	1 (min)	1.25 (max)	Vibration / Uncertainty	2.8 / 1.4 m/s <sup>2</sup>
Length (mm)	15 (min)	55 (max)		
Head (mm)	2 (min)	2 (max)		