















# BT1855-E KIT BRAD NAILER-CT/ST 55MM MAX

**BT13**

Diameter: 1 - 1.25mm  
Length: 15 - 55mm



## Features

- |   |   |   |  |
|---|---|---|--|
|  Magnesium Housing  |  Rubber Comfort Grip |  No-Mar-Tip      |  Dial-A-Depth         |
|  Anti Slip Bumpers |  Oil Free Engine    |  Rear Exhaust   |  Compact Nose        |
|  Side Loading     |  Carry Case        |  Tool Lock-Out |  Selectable Trigger |
|  Locking Trigger  |  Belt Hook         |   |  |

## SPECIFICATION

|                         |           |            |  |                            |
|-------------------------|-----------|------------|--|----------------------------|
| Power type              | Pneumatic |            | Operating pressure                     | 4.80 - 8.30 BAR            |
| Weight                  | 1.23 kg   |            |  | 70.00 - 120.00 PSI         |
| Width                   | 70 mm     |            | Air Consumption Ltr.per shot @ 5.6 bar | 1.33                       |
| Length                  | 235 mm    |            | Air fitting thread type                | 1/4 BSP                    |
| Height                  | 240 mm    |            | Noise                                  | <b>LPA 1sd</b> 83.20       |
| Magazine capacity (max) | 100       |            |  | <b>LWA 1sd</b> 88.50       |
| BT13 Series Fasteners:  |           |            |  | <b>LPA 1s, 1m</b> 75.50    |
| Diameter (mm)           | 1 (min)   | 1.25 (max) | Vibration / Uncertainty                | 2.8 / 1.4 m/s <sup>2</sup> |
| Length (mm)             | 15 (min)  | 55 (max)   |  |                            |
| Head (mm)               | 2 (min)   | 2 (max)    |  |                            |