

# CF15-1-E

## CORRUGATED FASTENER TOOL-CT 15MM MAX



Crown: 24.4 - 24.4mm  
Length: 10 - 15mm



### Features



Magnesium Housing



Rubber Comfort Grip



Adjustable Exhaust



Contact Trip



Anti Slip Bumpers



Push Magazine Adjustment

### SPECIFICATION

|                         |            |            |  |                               |
|-------------------------|------------|------------|--|-------------------------------|
| Power type              | Pneumatic  |            | Operating pressure                     | 4.80 - 8.30 BAR               |
| Weight                  | 2.65 kg    |            |  | 65.00 - 120.00 PSI            |
| Width                   | 89 mm      |            | Air Consumption Ltr.per shot @ 5.6 bar | 2.14                          |
| Length                  | 291 mm     |            | Air fitting thread type                | 1/4 BSP                       |
| Height                  | 277 mm     |            | Noise                                  | <b>LPA 1sd</b> 93.64          |
| Magazine capacity (max) | 100        |            |  | <b>LWA 1sd</b> 99.56          |
| CF Series Fasteners:    |            |            |  | <b>LPA 1s, 1m</b> 86.56       |
| Crown (mm)              | 24.4 (min) | 24.4 (max) | Vibration / Uncertainty                | 4.29 / 2.145 m/s <sup>2</sup> |
| Length (mm)             | 10 (min)   | 15 (max)   |  |                               |