

# F28WW-E


## 28° WWELD STICK NAILER-ST +CASE





Diameter: 2.8 - 3.3mm  
Length: 50 - 90mm





### Features


- 


Magnesium Housing
- 


Rubber Comfort Grip
- 


Serrated Tip
- 


No-Mar-Tip
- 

Dial-A-Depth
- 

Push Button Depth Control
- 

Sequential Trip
- 

Anti Slip Bumpers
- 

Compact Nose
- 

Carry Case

### SPECIFICATION

Power type	Pneumatic	Operating pressure	4.80 - 8.30 BAR
Weight	3.50 kg		70.00 - 120.00 PSI
Width	133 mm	Air Consumption Ltr.per shot @ 5.6 bar	2.47
Length	508 mm	Air fitting thread type	1/4 BSP
Height	355 mm	Noise	<b>LPA 1sd</b> 96.30
Magazine capacity (max)	90		<b>LWA 1sd</b> 100.10
WW 28 Series Fasteners:			<b>LPA 1s, 1m</b> 87.10
Diameter (mm)	2.8 (min)      3.3 (max)	Vibration / Uncertainty	2.47 / N/A m/s <sup>2</sup>
Length (mm)	50 (min)      90 (max)		
Head (mm)	7.5 (min)      7.5 (max)		
Collation type	Wire weld		
Collation angle	28		