

IC50-2-E

COIL NAILER-ST 50MM MAX



Diameter: 1.6 - 2.5mm
Length: 25 - 50mm



Features



Rubber Comfort Grip



Dial-A-Depth



Adjustable Exhaust



Sequential Trip



Impact Resistant Magazine



Twist Magazine



Dust & Debris Guard

SPECIFICATION

| | | | | |
|-------------------------|-----------|-----------|--|------------------------------|
| Power type | Pneumatic | | Operating pressure | 4.9 - 8.4 BAR |
| Width | 305 mm | | | 71 - 122 PSI |
| Length | 285 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 1.55 |
| Height | 128 mm | | Noise | LPA 1sd 91.9 |
| Jaw depth | 2.0 | | | LWA 1sd 95.5 |
| Magazine capacity (max) | 300-350 | | | LPA 1s, 1m 82.5 |
| N Series Fasteners: | | | Vibration / Uncertainty | 2.74 / 1.37 m/s ² |
| Diameter (mm) | 1.6 (min) | 2.5 (max) | | |
| Length (mm) | 25 (min) | 50 (max) | | |
| Head (mm) | 4.2 (min) | 5.6 (max) | | |
| Collation angle | 15 | | | |