

# MIII812CNCT

## CONCRETE T NAILER-CT



Diameter: 2.5 - 2.5mm  
Length: 19 - 60mm



### Features



Aluminium Housing



Adjustable Exhaust



Contact Trip

| SPECIFICATION           |           |           |                                        |                 |
|-------------------------|-----------|-----------|----------------------------------------|-----------------|
| Power type              | Pneumatic |           | Shots per charge                       |                 |
| Weight                  | 3.23 kg   |           | Operating pressure                     | 4.20 - 7.00 BAR |
| Width                   | 70 mm     |           | 60.00 - 100.00 PSI                     |                 |
| Length                  | 275 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar | 2.01            |
| Height                  | 325 mm    |           | Air fitting thread type                | 3/8 BSP         |
| Magazine capacity (max) | 66        |           | Noise                                  | LPA 1sd76.30    |
| T250 Series Fasteners:  |           |           | LWA 1sd                                | 82.70           |
| Diameter (mm)           | 2.5 (min) | 2.5 (max) | LPA 1s, 1m                             | 69.70           |
| Length (mm)             | 19 (min)  | 60 (max)  | Vibration / Uncertainty                |                 |
| Head (mm)               | 5 (min)   | 5 (max)   | 3.23 / 1.615 m/s2                      |                 |
| Collation angle         | 0         |           |                                        |                 |