

# N64084-1-E

## COIL NAILER-CT 64MM MAX



Diameter: 2.03 - 2.5mm  
Length: 30 - 65mm



### Features



Aluminium Housing



Rubber Comfort Grip



Adjustable Exhaust



Contact Trip



Steel Frame Protectors



Bench Stability



Impact Resistant Magazine



Compact Nose



Twist Magazine



Dust & Debris Guard



Hanging Port

### SPECIFICATION

|                         |                           |                                        |                               |
|-------------------------|---------------------------|----------------------------------------|-------------------------------|
| Power type              | Pneumatic                 | Operating pressure                     | 4.80 - 8.30 BAR               |
| Weight                  | 2.63 kg                   |                                        | 70.00 - 120.00 PSI            |
| Width                   | 133 mm                    | Air Consumption Ltr.per shot @ 5.6 bar | 1.21                          |
| Length                  | 266 mm                    | Air fitting thread type                | 1/4 BSP                       |
| Height                  | 327 mm                    | Noise                                  | <b>LPA 1sd</b> 92.90          |
| Magazine capacity (max) | 350                       |                                        | <b>LWA 1sd</b> 98.80          |
| N Series Fasteners:     |                           |                                        | <b>LPA 1s, 1m</b> 85.80       |
| Diameter (mm)           | 2.03 (min)      2.5 (max) | Vibration / Uncertainty                | 2.75 / 1.375 m/s <sup>2</sup> |
| Length (mm)             | 30 (min)      65 (max)    |                                        |                               |
| Head (mm)               | 4.5 (min)      4.5 (max)  |                                        |                               |
| Collation angle         | 15                        |                                        |                               |