

# N64084-2-E


## COIL NAILER-ST 64MM MAX





Diameter: 2.03 - 2.5mm  
Length: 30 - 65mm





### Features


- 


Aluminium Housing
- 


Rubber Comfort Grip
- 


Adjustable Exhaust
- 


Sequential Trip
- 


Steel Frame Protectors
- 

Bench Stability
- 

Impact Resistant Magazine
- 

Compact Nose
- 

Twist Magazine
- 

Dust & Debris Guard
- 

Hanging Port

### SPECIFICATION

Power type	Pneumatic	Operating pressure	4.80 - 8.30 BAR
Weight	2.63 kg		70.00 - 120.00 PSI
Width	133 mm	Air Consumption Ltr.per shot @ 5.6 bar	1.21
Length	266 mm	Air fitting thread type	1/4 BSP
Height	327 mm	Noise	<b>LPA 1sd</b> 92.90
Magazine capacity (max)	350		<b>LWA 1sd</b> 98.80
N Series Fasteners:			<b>LPA 1s, 1m</b> 85.80
Diameter (mm)	2.03 (min)      2.5 (max)	Vibration / Uncertainty	2.75 / 1.375 m/s <sup>2</sup>
Length (mm)	30 (min)      65 (max)		
Head (mm)	4.5 (min)      4.5 (max)		
Collation angle	15		