

RN46K-1-E










ROOFING NAILER-CT 45MM



Diameter: 3.05 - 3.4mm
Length: 19 - 45mm



Features

-  Magnesium Housing
-  Rubber Comfort Grip
-  Dial-A-Depth
-  Contact Trip
-  Steel Frame Protectors
-  Anti Slip Bumpers
-  Side Loading
-  Impact Resistant Magazine
-  Twist Magazine

SPECIFICATION

| | | | |
|-------------------------|----------------------------|--|------------------------------|
| Power type | Pneumatic | Operating pressure | 4.80 - 7.00 BAR |
| Weight | 2.70 kg | | 70.00 - 100.00 PSI |
| Width | 117 mm | Air Consumption Ltr.per shot @ 5.6 bar | 1.1 |
| Length | 277 mm | Air fitting thread type | 1/4 BSP |
| Height | 270 mm | Noise | LPA 1sd 76.30 |
| Magazine capacity (max) | 120 | | LWA 1sd 82.70 |
| CR Series Fasteners: | | | LPA 1s, 1m 69.70 |
| Diameter (mm) | 3.05 (min) 3.4 (max) | Vibration / Uncertainty | 3.04 / 1.52 m/s ² |
| Length (mm) | 19 (min) 45 (max) | | |
| Head (mm) | 10.1 (min) 10.1 (max) | | |
| Collation angle | 15 | | |