

SB-1850BN

BRAD NAILER-ST 50MM MAX



Diameter: 1 - 1.25mm
Length: 15 - 50mm



Features



Aluminium Housing



Rubber Comfort Grip



No-Mar-Tip



Dial-A-Depth



Adjustable Exhaust



Sequential Trip



Side Loading



Carry Case

SPECIFICATION

| | | | | |
|-------------------------|-----------|------------|--|------------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 1.22 kg | | Operating pressure | 5.00 - 7.00 BAR |
| Width | 51 mm | | | 75.00 - 100.00 PSI |
| Length | 235 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 0.73 |
| Height | 241 mm | | Air fitting thread type | 1/4 BSP |
| Magazine capacity (max) | 100 | | Noise | LPA 1sd 88.30 |
| BT13 Series Fasteners: | | | | LWA 1sd 91.80 |
| Diameter (mm) | 1 (min) | 1.25 (max) | | LPA 1s, 1m 78.80 |
| Length (mm) | 15 (min) | 50 (max) | Vibration / Uncertainty | < 2.5 / N/A m/s ² |
| Head (mm) | 2 (min) | 2 (max) | | |