

SL125OC-2

SL STAPLER OUTWARD CLINCH



Diameter: 0.9 - 1.3mm
 Crown: 8 - 8mm
 Length: 12 - 38mm



Features



Magnesium Housing



Rubber Comfort Grip



Dial-A-Depth



Sequential Trip



Oil Free Engine



Rear Exhaust



Bottom Loading



Outward Clinch

SPECIFICATION

| | | | | |
|-------------------------|-----------|-----------|--|------------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 1.00 kg | | Operating pressure | 4.80 - 8.30 BAR |
| Width | 59.7 mm | | | 70.00 - 120.00 PSI |
| Length | 257.1 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 0.9 |
| Height | 204.7 mm | | Air fitting thread type | 1/4 BSP |
| Magazine capacity (max) | 110 | | Noise | LPA 1sd 86.68 |
| SL Series Fasteners: | | | | LWA 1sd 91.83 |
| Diameter (mm) | 0.9 (min) | 1.3 (max) | | LPA 1s, 1m 78.83 |
| Crown (mm) | 8 (min) | 8 (max) | Vibration / Uncertainty | 2.74 / 1.37 m/s ² |
| Length (mm) | 12 (min) | 38 (max) | | |