

SL1838BC-E BOSTITCH CAP STAPLER KIT



Diameter: 0.9 - 1.3mm
Crown: 8 - 8mm
Length: 19 - 38mm



Diameter: 25 - 25mm
Crown: 25 - 25mm



Features



Magnesium Housing



Rubber Comfort Grip



Anti Slip Bumpers



Oil Free Engine



Rear Exhaust

SPECIFICATION

| | | | | |
|---------------------------|-----------|-----------|--|--------------------------------|
| Power type | Pneumatic | | Operating pressure | 4.80 - 8.30 BAR |
| Weight | 1.77 kg | | | 70.00 - 120.00 PSI |
| Width | 159 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 1.33 |
| Length | 286 mm | | Air fitting thread type | 1/4 BSP |
| Height | 267 mm | | Noise | LPA 1sd 86.59 |
| Magazine capacity (max) | 100 | | | LWA 1sd 94.16 |
| SL Series Fasteners: | | | | LPA 1s, 1m 81.20 |
| Diameter (mm) | 0.9 (min) | 1.3 (max) | Vibration / Uncertainty | 2.944 / 1.472 m/s ² |
| Crown (mm) | 8 (min) | 8 (max) | | |
| Length (mm) | 19 (min) | 38 (max) | | |
| SB-CAPS Series Fasteners: | | | | |
| Diameter (mm) | 25 (min) | 25 (max) | | |
| Crown (mm) | 25 (min) | 25 (max) | | |