

# SX150-1

## SX STAPLER-CT 32MM MAX



Diameter: 0.9 - 1.3mm  
 Crown: 5.6 - 5.6mm  
 Length: 12 - 38mm



### Features



Magnesium Housing



Rubber Comfort Grip



Contact Trip



Oil Free Engine



Rear Exhaust



Rear Loading

### SPECIFICATION

|                         |           |           |  |                               |
|-------------------------|-----------|-----------|--|-------------------------------|
| Power type              | Pneumatic |           | Shots per charge                       |                               |
| Weight                  | 1.00 kg   |           | Operating pressure                     | 4.80 - 8.30 BAR               |
| Width                   | 59.7 mm   |           |  | 70.00 - 120.00 PSI            |
| Length                  | 257.1 mm  |           | Air Consumption Ltr.per shot @ 5.6 bar | 0.9                           |
| Height                  | 244.5 mm  |           | Air fitting thread type                | 1/4 BSP                       |
| Magazine capacity (max) | 110       |           | Noise                                  | <b>LPA 1sd</b> 75.50          |
| SX Series Fasteners:    |           |           |  | <b>LWA 1sd</b> 80.20          |
| Diameter (mm)           | 0.9 (min) | 1.3 (max) |  | <b>LPA 1s, 1m</b> 67.20       |
| Crown (mm)              | 5.6 (min) | 5.6 (max) | Vibration / Uncertainty                | 3.03 / 1.515 m/s <sup>2</sup> |
| Length (mm)             | 12 (min)  | 38 (max)  |  |                               |