

SX1838-E














KIT SX STAPLER-CT/ST 38MM MAX



Diameter: 0.9 - 1.3mm
Crown: 5.6 - 5.6mm
Length: 12 - 38mm



Features

- 
Mg
 Magnesium Housing
- 
 Rubber Comfort Grip
- 
 No-Mar-Tip
- 
 DIAL-A
 Dial-A-Depth
- 
 Anti Slip Bumpers
- 
 Oil Free Engine
- 
 Rear Exhaust
- 
 Compact Nose
- 
 Bottom Loading
- 
 Carry Case
- 
 Tool Lock-Out
- 
 CT
ST
 Selectable Trigger
- 
 Locking Trigger

SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.36 kg			70.00 - 120.00 PSI
Width	70 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.33
Length	235 mm		Air fitting thread type	1/4 BSP
Height	240 mm		Noise	LPA 1sd 81.34
Magazine capacity (max)	100			LWA 1sd 87.50
SX Series Fasteners:				LPA 1s, 1m 75.50
Diameter (mm)	0.9 (min)	1.3 (max)	Vibration / Uncertainty	3.06 / 1.53 m/s ²
Crown (mm)	5.6 (min)	5.6 (max)		
Length (mm)	12 (min)	38 (max)		