

# TU-216-71-E

## 71 STAPLER 16MM MAX (TU-216)

72

Diameter: 0.6 - 0.7mm  
Crown: 9.1 - 9.1mm  
Length: 4 - 16mm



### Features



Aluminium Housing



Rubber Comfort Grip



Power Adjustment



Secondary Trigger



Rear Exhaust



Bottom Loading

### SPECIFICATION

|                         |           |           |  |                              |
|-------------------------|-----------|-----------|--|------------------------------|
| Power type              | Pneumatic |           | Shots per charge                       |                              |
| Weight                  | 0.85 kg   |           | Operating pressure                     | 4.90 - 8.40 BAR              |
| Width                   | 40 mm     |           |  | 80.00 - 120.00 PSI           |
| Length                  | 221 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar | 0.17                         |
| Height                  | 150 mm    |           | Air fitting thread type                | 1/4 BSP                      |
| Magazine capacity (max) | 172       |           | Noise                                  | <b>LPA 1sd</b> 64.40         |
| 72 Series Fasteners:    |           |           |  | <b>LWA 1sd</b> 74.00         |
| Diameter (mm)           | 0.6 (min) | 0.7 (max) |  | <b>LPA 1s, 1m</b> 61.00      |
| Crown (mm)              | 9.1 (min) | 9.1 (max) | Vibration / Uncertainty                | < 2.5 / N/A m/s <sup>2</sup> |
| Length (mm)             | 4 (min)   | 16 (max)  |  |                              |