

TU-216-84-E

84 STAPLER 16MM MAX (TU-216)

84

Diameter: 0.5 - 1mm
 Crown: 12.3 - 12.3mm
 Length: 4 - 16mm



Features



Aluminium Housing



Rubber Comfort Grip



Power Adjustment



Secondary Trigger



Rear Exhaust



Bottom Loading

SPECIFICATION

| | | | | |
|-------------------------|------------|------------|--|------------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 0.83 kg | | Operating pressure | 4.90 - 8.40 BAR |
| Width | 40 mm | | | 80.00 - 120.00 PSI |
| Length | 221 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 0.17 |
| Height | 150 mm | | Air fitting thread type | 1/4 BSP |
| Magazine capacity (max) | 125 | | Noise | LPA 1sd 64.40 |
| 84 Series Fasteners: | | | | LWA 1sd 74.00 |
| Diameter (mm) | 0.5 (min) | 1 (max) | | LPA 1s, 1m 61.00 |
| Crown (mm) | 12.3 (min) | 12.3 (max) | Vibration / Uncertainty | < 2.5 / N/A m/s ² |
| Length (mm) | 4 (min) | 16 (max) | | |